




气动抽废油机

AIR-OPERATED SUCTION-DRAINER

通过量杯及罐体直接产生负压吸油的抽废油机
(注：不能抽取带有腐蚀性的液体)。

The waste oil extractor generates negative pressure through the measuring cup and tank to absorb oil (note: corrosive liquid is not allowed).



技术参数
Technical parameters

型号 Model	43025	43035
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
排油压力 Max pressure for draining	0.5bar	0.5bar
罐体容积 Tank capacity	25L	25L
量杯容积 Prechamber capacity	-	10L
耗气量 Average air consumption	200L/min	200L/min
工作压力 Air working pressure	6-8bar	6-8bar
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80°C	< 80°C
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	530*450*680mm	530*450*680mm
包装尺寸2 Packing size_2	-	240*240*470mm
产品重量 Gross weight	12kg	16kg




接废油机

GRAVITY WASTE OIL COLLECTING KIT

利用重力收集废油的装置。

The waste oil drainer is suitable for gravity drainage of engine.



技术参数
Technical parameters

型号 Model	41075	41220
接油高度 MAX lifting height	1.6m	1.6m
接油范围 Scope of oil collecting	580m	580m
拖车适用油桶 Trolley capacity	50-60L	180-220L
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	1315*290*145mm	1315*290*145mm
包装尺寸2 Packing size_2	545*495*195mm	870*700*115mm
产品重量 Gross weight	15.6kg	25.8kg



气动抽废油机


AIR-OPERATED SUCTION-DRAINER

通过量杯及罐体直接产生负压吸油的抽废油机（注：不能抽取带有腐蚀性的液体）。

The waste oil extractor generates negative pressure through the measuring cup and tank to absorb oil (note: corrosive liquid is not allowed).

技术参数
Technical parameters

型号 Model	43075E	43090E
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
排油压力 Max pressure for draining	0.5bar	0.5bar
罐体容积 Tank capacity	70L	85L
量杯容积 Prechamber capacity	10L	10L
耗气量 Average air consumption	200L/min	200L/min
工作压力 Air working pressure	6-8bar	6-8bar
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80°C	< 80°C
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	240*240*470mm	240*240*470mm
包装尺寸2 Packing size_2	470*470*880mm	470*470*1010mm
产品重量 Gross weight	23.8kg	26kg



气动抽废油机


AIR-OPERATED SUCTION-DRAINER

通过量杯及罐体直接产生负压，可手动平衡量杯罐体真空，让量杯罐体真空一体吸油的抽废油机，其真空容量更大，抽油更快更久，可脱离气源工作。（注：不能抽取带有腐蚀性的液体）。

The negative pressure is directly generated through the measuring cup and the tank, and vacuum of the measuring cup and tank can be manually balanced, so that the waste oil extractor that allows the measuring cup and tank to absorb oil together with a larger vacuum capacity, faster and longer oil extraction, and can work without air source. (note: corrosive liquid is not allowed).

技术参数
Technical parameters

型号 Model	43075H	43090H
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
排油压力 Max pressure for draining	0.5bar	0.5bar
罐体容积 Tank capacity	70L	85L
量杯容积 Prechamber capacity	10L	10L
耗气量 Average air consumption	200L/min	200L/min
工作压力 Air working pressure	6-8bar	6-8bar
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80°C	< 80°C
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	240*240*470mm	240*240*470mm
包装尺寸2 Packing size_2	470*470*880mm	470*470*1010mm
产品重量 Gross weight	24kg	26.2kg



气动抽废油机


AIR-OPERATED SUCTION-DRAINER

配备抗腐蚀、不龟裂、不漏气的金刚不坏量杯，量杯及罐体直接产生负压，可手动平衡量杯罐体真空，让量杯罐体真空一体吸油的抽废油机，其真空容量更大，抽油更快更久，可脱离气源工作。

Equipped with a high borosilicate glass measuring cup that is corrosion-resistant, crack-free, and air-tight, the measuring cup and the tank directly generate negative pressure, and the vacuum of the measuring cup and tank can be manually balanced, so that the waste oil extractor that allows the measuring cup and tank to absorb oil together with a larger vacuum capacity, faster and longer oil extraction, and can work without air source.

技术参数
Technical parameters


型号 Model	43075D	43090D
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
排油压力 Max pressure for draining	0.5bar	0.5bar
罐体容积 Tank capacity	70L	85L
量杯容积 Prechamber capacity	10L	10L
耗气量 Average air consumption	200L/min	200L/min
工作压力 Air working pressure	6-8bar	6-8bar
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80°C	< 80°C
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	240*240*470mm	240*240*470mm
包装尺寸2 Packing size_2	470*470*880mm	470*470*1010mm
产品重量 Gross weight	23.8kg	26kg



气动接废油机

AIR-OPERATED OIL COLLECTING DRAINER

利用重力收集费油的装置。
The waste oil drainer is suitable for gravity drainage of engine.



技术参数
Technical parameters

型号 Model	42080E	42095E
接油高度 MAX lifting height	1.6m	1.6m
罐体容积 Tank capacity	70L	85L
接油范围 Scope of oil collecting	580mm	580mm
排油压力 Max pressure for draining	0.5bar	0.5bar
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸 Packing size	470*470*880mm	470*470*1010mm
产品重量 Gross weight	23.8kg	26kg



气动抽接废油机

AIR-OPERATED OIL COLLECTING SUCTION-DRAINER


通过罐体直接产生负压吸油的抽废油机（注：不能抽取带有腐蚀性的液体）。

waste oil extractor that directly generates negative pressure to absorb oil through the tank (note: corrosive liquid is not allowed).

技术参数

Technical parameters

型号 Model	44080E	44095E
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
接油高度 MAX lifting height	1.35-1.75m	1.35-1.85m
罐体容积 Tank capacity	70L	85L
接油范围 Scope of oil collecting	580mm	580mm
排油压力 Max pressure for draining	0.5bar	0.5bar
工作压力 Air working pressure	6-8bar	6-8bar
耗气量 Average air consumption	200L/min	200L/min
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸 Packing size	470*470*880mm	470*470*1010mm
产品重量 Gross weight	24.8kg	27kg




气动抽接废油机

AIR-OPERATED OIL COLLECTING SUCTION-DRAINER

通过量杯及罐体直接产生负压吸油的抽废油机（注：不能抽取带有腐蚀性的液体）。

The waste oil extractor generates negative pressure through the measuring cup and tank to absorb oil (note: corrosive liquid is not allowed).



型号 Model	44090E	44105E
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
接油高度 MAX lifting height	1.35-1.75m	1.35-1.85m
罐体容积 Tank capacity	70L	85L
量杯容积 Prechamber capacity	10L	10L
接油范围 Scope of oil collecting	580mm	580mm
排油压力 Max pressure for draining	0.5bar	0.5bar
工作压力 Air working pressure	6-8bar	6-8bar
耗气量 Average air consumption	200L/min	200L/min
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	470*470*880mm	470*470*1010mm
包装尺寸2 Packing size_2	240*240*470mm	240*240*470mm
产品重量 Gross weight	27.5kg	29.7kg




气动抽接废油机

AIR-OPERATED OIL COLLECTING SUCTION-DRAINER
(PATENT NEW PRODUCT)

通过量杯及罐体直接产生负压，可手动平衡量杯罐体真空，让量杯罐体真空一体吸油的抽废油机，其真空容量更大，抽油更快更久，可脱离气源工作。（注：不能抽取带有腐蚀性的液体）。

The negative pressure is directly generated through the measuring cup and the tank, and vacuum of the measuring cup and tank can be manually balanced, so that the waste oil extractor that allows the measuring cup and tank to absorb oil together with a larger vacuum capacity, faster and longer oil extraction, and can work without air source. (note: corrosive liquid is not allowed).



型号 Model	44090H	44105H
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
接油高度 MAX lifting height	1.35-1.75m	1.35-1.85m
罐体容积 Tank capacity	70L	85L
量杯容积 Prechamber capacity	10L	10L
接油范围 Scope of oil collecting	580mm	580mm
排油压力 Max pressure for draining	0.5bar	0.5bar
工作压力 Air working pressure	6-8bar	6-8bar
耗气量 Average air consumption	200L/min	200L/min
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	470*470*880mm	470*470*1010mm
包装尺寸2 Packing size_2	240*240*470mm	240*240*470mm
产品重量 Gross weight	28.6kg	30.8kg




气动抽接废油机

AIR-OPERATED OIL COLLECTING SUCTION-DRAINER
(PATENT NEW PRODUCT)

配备抗腐蚀、不龟裂、不漏气的金刚不坏量杯，量杯及罐体直接产生负压，可手动平衡量杯罐体真空，让量杯罐体真空一体吸油的抽废油机，其真空容量更大，抽油更快更久，可脱离气源工作。

Equipped with a high borosilicate glass measuring cup that is corrosion-resistant, crack-free, and air-tight, the measuring cup and the tank directly generate negative pressure, and and vacuum of the measuring cup and tai can be manually balanced, so that the waste oil extractor that allows the measuring cup and tank to absorb oil together with a larger vacuum capac faster and longer oil extraction, and can work without air source.



型号 Model	44090D	44105D
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
接油高度 MAX lifting height	1.35-1.75m	1.35-1.85m
罐体容积 Tank capacity	70L	85L
量杯容积 Prechamber capacity	10L	10L
接油范围 Scope of oil collecting	580mm	580mm
排油压力 Max pressure for draining	0.5bar	0.5bar
工作压力 Air working pressure	6-8bar	6-8bar
耗气量 Average air consumption	200L/min	200L/min
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	470*470*880mm	470*470*1010mm
包装尺寸2 Packing size_2	240*240*470mm	240*240*470mm
产品重量 Gross weight	28.6kg	30.8kg



气动抽废油机

AIR-OPERATED SUCTION-DRAINER

通过罐体直接产生负压吸油的抽废油机（注：不能抽取带有腐蚀性的液体）。
The air-operated drainer is used for changing engine oil of any motor vehicle by means of vacuum or depression. Not available for brake fluids, fuels, flammable or corrosive liquids.

技术参数
Technical parameters

型号 Model	43065	43080
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
排油压力 Max pressure for draining	0.5bar	0.5bar
罐体容积 Tank capacity	70L	85L
耗气量 Average air consumption	200L/min	200L/min
工作压力 Air working pressure	6-8bar	6-8bar
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸 Packing size	470*470*880mm	470*470*880mm
产品重量 Gross weight	19kg	21.2kg




气动抽接废油机

AIR OPERATED OIL COLLECTING MACHINE

带有侧向托盘，可用于商用车的抽接两用机。
（注：不能抽取带有腐蚀性的液体）

The device is equipped with lateral tray. It may be applicable for pumping and picking of commercial vehicle. The corrosive liquids may be not pumped.




型号 Model	44110	44120
抽油速度 Suction rate	1.8-3.0L/min	1.8-3.0L/min
接油高度 MAX lifting height	1.5m	1.5m
罐体容积 Tank capacity	85L	85L
量杯容积 Prechamber capacity	450*375*120mm	450*375*120mm
接油范围 Scope of oil collecting	580mm	580mm
排油压力 Max pressure for draining	0.5bar	0.5bar
工作压力 Air working pressure	6-8bar	6-8bar
耗气量 Average air consumption	200L/min	200L/min
抽油管长 Length of suction hose	1.6m	1.6m
排油管长 Length of discharging hose	1.6m	1.6m
抽油最高温度 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	475*475*840mm	475*475*840mm
包装尺寸2 Packing size_2	575*470*140mm	575*470*140mm
包装尺寸3 Packing size_3	-	240*240*470mm
包装尺寸4 Packing size_4	1400*100*100mm	1400*100*100mm
产品重量 Gross weight	39kg	44kg



电动抽废油机

ELECTRIC OIL SUCTION-DRAINER

使用电动齿轮泵抽吸油的装置。
The suction-drainer, equipped with electric pump, is used to suck petrol or engine oil of any motor vehicle.





型号 Model	4007C	40080
抽油速度 Suction rate	0-8L/min	0-8L/min
电压 Working voltage	220V	220V
油壶容积 Oilcan capacity	70L	80L
量杯容积 Prechamber capacity	-	10L
排油压力 Max pressure for draining	0.5bar	0.5bar
抽油管长 Length of suction hose	1.5m	1.5m
抽油最高油温 MAX temperature of sucking oil	< 80℃	< 80℃
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	240*240*470mm	240*240*470mm
包装尺寸2 Packing size_2	600*490*815mm	600*490*815mm
产品重量 Gross weigh	40kg	40kg

专用接油小车

WASTE OIL COLLECTING PIT

带轮子可移动的接油小车，配有吸油接头。

The waste oil pit with wheels, equipped with draining oil filter and oil suction, is suitable for gravity draining of engine, gearbox and different oil from any motor vehicle.



型号 Model	42030	42031	42050	42051
接油量 Container capacity	30L	30L	50L	50L
包装形式 Package type	纸箱 Carton	纸箱 Carton	纸箱 Carton	纸箱 Carton
包装尺寸 Packing size	670*510*280mm	750*460*200mm	860*660*280mm	960*600*200mm
产品重量 Gross weight	15kg	22.5kg	15kg	22.5kg

壁装式强力抽废油套件

WALL-MOUNTED OIL PUMP DRAINER

使用气动废油泵抽油的壁装式套件。
The wall-mounted suction drainer, equipped with air-operated pump, is suitable for sucking and delivering waste oil, similar liquids etc.

型号 Model	45100	45110
比率 Ratio	1: 1	1: 1
进气嘴接头 Air inlet connection	1/4"	1/4"
出油口接头 Fluid outlet connection	1/2"	1/2"
工作压力 Air working pressure	5-8bar	5-8bar
最大压力 Maximum pressure	8bar	8bar
耗气量 Average air consumption	230L/min	230L/min
输送速度 Flow rate	1-3L/min	1-3L/min
油温 Temperature of pumping oil	< 80°C	< 80°C
支架孔径 Wall-bracket diameter	54mm	54mm
真空度 Vacuum degree	-0.8-0bar	-0.8-0bar
抽油管长 Length of suction hose	2m	2m
排油管长 Length of discharging hose	2m	2m
探针管总成 Probes assembly	1套 Set	1套 Set
卷管器型式 Type of hose reel	-	重型旋转式 Heavy-duty fixed type
卷管器出油管长 Length of outlet reelpipe	-	10m
卷管器进油管长 Length of inlet reelpip	-	1.5m
卷管器管径 Diameter of reelpipe	-	3/8"
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	1345*190*155mm	1345*190*155mm
包装尺寸2 Packing size_2	-	560*540*245mm
产品重量 Gross weight	8kg	29.2kg

移动式强力抽废油机

MOBIL PUISSANT OIL PUMP DRAINER

使用气动废油泵抽油的拖车式套件。
The mobile suction drainer, equipped with air-operated pump and trolley, is suitable for sucking and delivering waste oil, similar liquids etc.

型号 Model	45160	45180
比率 Ratio	1: 1	1: 1
进气嘴接头 Air inlet connection	1/4"	1/4"
出油口接头 Fluid outlet connection	1/2"	1/2"
工作压力 Air working pressure	5-8bar	5-8bar
最大压力 Maximum pressure	8bar	8bar
耗气量 Average air consumption	230L/min	230L/min
输送速度 Flow rate	1-3L/min	1-3L/min
油温 Temperature of pumping oil	< 80°C	< 80°C
抽油管长 Length of suction hose	2m	2m
排油管长 Length of discharging hose	2m	2m
探针管总成 Probes assembly	1套 Set	1套 Set
真空度 Vacuum degree	- 0.8-0bar	- 0.8-0bar
拖车适用油桶 Oil drum for trailer	18-60L	180-220L
包装形式 Package type	纸箱 Carton	纸箱 Carton
包装尺寸1 Packing size_1	1345*190*155mm	1345*190*155mm
包装尺寸2 Packing size_2	540*490*190mm	870*700*115mm
产品重量 Gross weight	16.5kg	28kg

强力抽废油泵

PUISSANT OIL PUMP

配有特殊装置的气动油泵，可产生持续不断的真空，专用于抽吸废油。
The air-operated oil pump, equipped with special suction device, can pump and suck constantly to creat a complete vacuum, Ideal for waste oil draining.

型号 Model	45000
比率 Ratio	1: 1
进气嘴接头 Air inlet connection	1/4"
出油口接头 Fluid outlet connection	1/2"
工作压力 Air working pressure	5-8bar
最大压力 Maximum pressure	8bar
耗气量 Average air consumption	230L/min
输送速度 Flow rate	1-3L/min
油温 Temperature of pumping oil	< 80°C
包装形式 Package type	纸箱 Carton
包装尺寸 Packing size	1345*190*155mm
产品重量 Gross weight	4.8kg

接油盘

OIL COLLECTING TRAY

型号 Model	3881	3885
直径 Diameter	接油范围 Scope of oil collecting φ580mm	接油范围 Scope of oil collecting φ580mm

接油针管

OIL INJECTING NEEDLE

型号 Model	4660 4670	46000 4601 4602 4603	46001 4611 4612 4613	46002
技术参数	1套 Φ5mm Φ6mm Φ8mm	1套 Φ5mm Φ6mm Φ8mm		
吸油专用接头 Quick-release connector	塑料接头 Plastic probe	金属接头 Rigid probe	套筒 Sleeve	

抽油量杯

SUCTION OIL CHAMBER



型号 Model	3895D	3893	3892	3892E	3892H
	不带吸油管 and 发生器总成 Without suction hose and vacuum generator assembly.				

真空发生器

VACUUM GENERATOR




型号 Model	3870	3871	3841	3875
----------	------	------	------	------

集油盒

OIL COLLECTING BOX

油管

OIL PIPE



抽油管	排油管	放油管					
型号 Model	3850	2m	3860	2m	3835 0.8m	3830	3831



WASTE OIL RECYCLING SYSTEM

废油回收系统

